



DK50-10


DK50-10 Z
without soundproofing box

DK50-10 S
with soundproofing box

DK50-10 Z/M
without soundproofing box,
with membrane dryer MD

DK50-10 S/M
with soundproofing box,
with membrane dryer MD

- compact design
- 5-7, 6-8, 8-10 bar working pressure range
- dual frequency solution
- new valve plate, enhanced life time
- 51% - 100% duty cycle
- easy installation with quick connect air couplings
- hours run counter - option
- optional accessories including



Filters






Membrane dryer MD



Connect air couplings



Auto drain



Technical specification	DK50-10 Z	DK50-10 S	DK50-10 Z/M	DK50-10 S/M	
Nominal voltage / frequency	230/ 50/60, 115/ 60				V/ Hz
Motor performance	0,55				kW
Efficiency of compressor (Working pressure 5-7bar)	75(50Hz) / 85(60Hz)		58(50Hz) / 68(60Hz)		l.min ⁻¹ / 5bar
Efficiency of compressor (Working pressure 6-8bar)	70(50Hz) / 80(60Hz)		60(50Hz) / 70(60Hz)		l.min ⁻¹ / 6bar
Efficiency of compressor (Working pressure 8-10bar)	60(50Hz) / 70(60Hz)		50(50Hz) / 60(60Hz)		l.min ⁻¹ / 8bar
Air tank capacity	10				L
Mode of operation	51-100%				
Noise level	65(50Hz) / 66,5(60Hz)	49,5(50Hz) / 51(60Hz)	67(50Hz) / 68,5(60Hz)	51,5(50Hz) / 53(60Hz)	dB(A)
Weight	38	53	44	61	kg
Dimensions (w x l x h)	485x350x553	580x440x655	544x350x553	649x440x655	mm

Technical modifications are subject to change.



EKOM spol. s r.o.
Priemyselná 5031/18
921 01 PIEŠŤANY
Slovak Republic

tel.: +421 33 7967205
fax: +421 33 7967223
e-mail: ekom@ekom.sk
www.ekom.sk

