

DK50 2V MOBILE

Compressor designed for demanding air supply for laboratories, autosamplers, robots, printing / folding equipment and other industrial and laboratory applications

DK50 2V MOBILE

compressor DK50 2V in soundproofing box MOBILE with the automatic condensate drain and filtration set

DK50 2V/M MOBILE

compressor DK50 2V in soundproofing box MOBILE with the membrane dryer



Benefits

- mobile solution
- continuous operation
- higher level of air filtration
- silent operation
- interesting ratio efficiency/ dimensions
- suitable for under table placing
- output pressure adjustment
- easy to install and maintain

Technical specification	DK50 2V MOBILE	DK50 2V/M MOBILE
Nominal voltage (V/Hz)	230/ 50, 120/ 60	
Compressor efficiency (l.min ⁻¹ /6 bar)	134	105
Max. current (A)	6,5	
Motor performance (kW)	1,1	
Air tank capacity (l)	25	
Pressure range (bar)	6-8 (8-10)	
Mode of operation	S1	
Noise level (dB[A])	≤62	
Weight (kg)	96	
Dimensions (w x l x h)(mm)	580 x 700 x 860 mm	

Technical modifications are subject to change.



EKOM spol. s r.o.
Priemysel'na 5031/18
921 01 Piešťany
Slovak republic

tel.: +421 33 7967211
fax: +421 33 7967223
e-mail: ekom@ekom.sk
<http://www.ekom.sk>